



SUPERFLATLINE SPEAKER CABLE

The SuperFlatline Speaker Cable is a true Nordost classic. It was one of the original cable options that put Nordost on the map. Easily distinguishable by its trademark, flat design, SuperFlatline quickly became known throughout the industry as one of the most respected high end speaker cables, offering an unmatched performance level at its price point. This highly sought after product offers detail, clarity, and purity throughout the whole frequency spectrum, from subsonic lows to ultrasonic highs. Now, due to popular demand, Nordost's SuperFlatline cable is back!

Nordost's SuperFlatline Speaker Cable consists of 16, 23 AWG, solid core, flat, rectangular copper conductors. The flat geometry of this cable not only increases signal transfer speed, but also makes it possible to run lengths under carpets for easy and discreet installation. Additionally, SuperFlatline employs an innovative precision FEP extrusion process, which lowers the capacitance and increases the bandwidth of the cable dramatically, enhancing accuracy in signal transfer.

This high quality, versatile cable can be used in any system. When used in a shotgun configuration, the SuperFlatline is capable of carrying high currents (up to 12.5 amps at 300 volts) while its 16 conductors can easily facilitate bi-wiring or bi-amping. Like all Nordost Leifstyle products, SuperFlatline is sold to certified Nordost retailers in spools, alongside heatshrink and connector kits, which include Nordost's gold-plated Spade or Z-plug (banana) connectors. Selling this cable in spools makes it easier for Nordost dealers to serve their clients, by providing any length

of cabling needed to custom-fit their home theater or sound system. Thanks to the development of a proprietary tool designed to slit and strip the cable, installation of SuperFlatline is now even easier, allowing installers to cut a precise break out at any length.

Designed and manufactured entirely in the USA, the SuperFlatline Speaker Cable guarantees the precision of craftsmanship required to produce the uncolored, unfiltered accuracy of sound that is synonymous with Nordost.

- Made in the USA
- Extruded FEP Insulation
- 16 x 23 AWG flat rectangular conductors
- 14 AWG when in shotgun configuration
- 99.9999% OFC
- Propagation Delay: 91% speed of light
- RoHS Compliant



NORDOST

MAKING THE CONNECTION

Nordost 93 Bartzak Drive Holliston MA 01746 USA

Email: info@nordost.com
Website: www.nordost.com



Made in the USA